

---

# Description of the Argo GDAC File Checks: Data Format and Consistency Checks

---

Version 2.4  
June 2016

**ARGO**

*part of the integrated global observation strategy*



---

**ARGO**

*part of the integrated global observation strategy*



Argo data management

Description of the Argo GDAC File Checks

Authors: Mark Ignaszewski / FNMOC

**How to cite this document**

Mark Ignaszewski / FNMOC, **Description of the Argo GDAC File Checks: Data Format and Consistency Checks.** <http://dx.doi.org/xxx>

# Table of contents

---

<b>TABLE OF CONTENTS</b> .....	<b>3</b>
<b>HISTORY OF THE DOCUMENT</b> .....	<b>5</b>
<b>1 INTRODUCTION</b> .....	<b>6</b>
1.1 CHANGES FROM LAST REVISION .....	6
1.2 ITEMS TO NOTE/DISCUSS.....	6
1.3 PROPOSED CHANGES .....	6
<b>2 GDAC FILE NAME VALIDATION</b> .....	<b>6</b>
<b>3 FORMAT CHECKS</b> .....	<b>7</b>
3.1 PHYSICAL PARAMETER VARIABLES .....	7
3.2 EXCEPTIONS .....	8
<b>4 META-DATA DATA CONSISTENCY CHECKS</b> .....	<b>8</b>
4.1 REASONABLE DATE CHECKS .....	9
4.2 HIGHLY-DESIRABLE PARAMETER CHECKS (FILE-VERSION 2.3 AND EARLIER).....	9
4.3 MANDATORY PARAMETER CHECKS (FILE VERSION 2.4 AND LATER) .....	9
4.4 CONFIGURATION PARAMETER NAME CHECKS .....	10
<b>5 PROFILE DATA CHECKS</b> .....	<b>10</b>
5.1 META-DATA (WITHIN A PROFILE FILE) CHECKS .....	10
5.2 REASONABLE DATE CHECKS .....	11
5.3 PHYSICAL PARAMETER CHECKS .....	11
5.4 ADDITIONAL D-MODE FILE CHECKS .....	13
<b>6 TECHNICAL DATA CHECKS</b> .....	<b>14</b>
6.1 META-DATA CHECKS (WITHIN TECHNICAL FILE) .....	14
6.2 REASONABLE DATE CHECKS .....	14

6.3	TECHNICAL PARAMETER NAMES (FORMAT-VERSION 2.4 AND LATER) .....	14
6.4	***FOR FUTURE IMPLEMENTATION*** TECHNICAL PARAMETER VALUES.....	15
7	<u>TRAJECTORY DATA CHECKS</u> .....	15
7.1	META-DATA CHECKS .....	15
7.2	REASONABLE DATE CHECKS .....	16
7.3	N_MEASUREMENT VARIABLE GROUP CHECKS .....	16
7.4	N_CYCLE VARIABLE GROUP CHECKS.....ERREUR ! SIGNET NON DEFINI.	
	<u>APPENDIX A. ALLOWED EXCEPTIONS</u> .....	17
	DATA_TYPE SETTINGS: .....	17
	PRE-V3.1 FILES.....	17
	V3.1 FILES .....	17

# History of the document

Version	Date	Comment
1.0	November 2014	Original version sent around for comment
1.1	March 2015	Update D-mode checks when all values for a parameter are missing. Allow <*> in config and tech templates to match "empty"
1.3	October 2015	Update for profile checks (including bio-profile checks) Add "N_VALUES" description Add naming rules for "*2" variables Add proposed technical parameter value checks. Add proposed trajectory file consistency checks. Put document in standard Argo format.
1.4	December 2015	Incorporate comments from reviewers and ADMT-16 decisions, including... Bio-profile, intermediate parameter: <PARAM> cannot exist by itself (PROF_*_QC, and *_QC) must always be present. Bio-profile data checks are accepted (not just proposed). DATA_STATE_INDICATOR checks are accepted (not just proposed).
2.4	April 2016	File name validation has been added to the FileChecker. Add check of units for CONFIGURATION_PARAMETER_NAME settings. Add check that <PARAM>_ADJUSTED and <PARAM>_ADJUSTED_ERROR are set at the same levels for D-mode parameters. Allow <PARAM>_ADJUSTED_ERROR to be set for A-mode bio-parameters Remove comparison of DATE_UPDATE to GDAC receipt time in all files. Allow JULD and JULD_LOCATION to differ by 2 days (instead of 1) LAUNCH_DATE mandatory in meta-data files. Trajectory files: Meta-data, Reasonable Date, and TRAJECTORY_PARAMETERS checks have been implemented. Adjusted version number of the document to match the software version number.
2.4.1	May 2016	Add LAUNCH_CONFIG_PARAMETER_NAME to meta-data data checks. Add "deprecated name/unit" capability for meta_data and tech files
2.4.2	June 2016	Allow for alternate DIMENSION names in variables: Variables can be declared as Variable(dim1 dim2) To allow for either "dim1" or "dim2" to be used as a DIMENSION.

## 1 Introduction

Every Argo data file submitted by a DAC for distribution on the GDAC has its format and data consistency checked by the Argo FileChecker. Two types of checks are applied:

1. Format checks. Ensures the file formats match the Argo standards precisely.
2. Data consistency checks.

Additional data consistency checks are performed on a file after it **passes** the format checks. These checks do not duplicate any of the quality control checks performed elsewhere. These checks can be thought of as “sanity checks” to ensure that the data are consistent with each other.

The data consistency checks enforce data standards and ensure that certain data values are reasonable and/or consistent with other information in the files. Examples of the “data standard” checks are the “mandatory parameters” defined for meta-data files and the technical parameter names in technical data files.

Files with format or consistency errors are rejected by the GDAC and are not distributed. Less serious problems will generate warnings and the file will still be distributed on the GDAC.

Reference Tables and Data Standards:

Many of the consistency checks involve comparing the data to the published reference tables and data standards. These tables are documented in the User’s Manual. (The FileChecker implements “text versions” of these tables.)

### 1.1 Changes from last revision

Changes to the tests from the last revision will be highlighted as shown: **Changes to tests**. Editorial changes are not highlighted.

### 1.2 Items to Note/Discuss

Items that should be discussed (in my opinion) have been highlighted as shown: **Items to be noted and/or discussed**.

### 1.3 Proposed Changes

There are proposed changes included in this document. These are highlighted with as shown: **Proposed changes**.

## 2 GDAC File Name Validation

The FileChecker validates that the name of the file submitted to the GDAC conforms to the standard documented in the Users Manual based on the data contained within the data file. If the submitted file name does not match the expected file name, the file is rejected. (In practice, this check is performed after the format and data checks documented below.)

### 3 Format Checks

The FileChecker compares the netCDF file structure of submitted files with the format specification documented in the Argo Data Management User's Manual. The format checking process is very strict about compliance with the documented specification.

NOTE: "Format Version" versus "Manual Version".

The term "format-version" refers specifically to the `FORMAT_VERSION` documented for each file type in the User's Manual. When referring to a specific version of the User's Manual the term "manual-version" will be used.

Multiple format-versions of a given file type (meta-data, profile, etc) are accepted by the FileChecker. This is done to provide DACs sufficient time to transition from one format-version to another. The ADMT will determine when an older format-version should no longer be accepted and the FileChecker will be re-configured to reject any subsequent files received in that version.

The format checking process is the same for each type of data file. The process compares:

1. Global attributes
2. Dimensions: The dimensions specified in the User's Manual, and only those dimensions, must be present in the data file.

For dimensions that represent constants, such as the `STRING*` dimensions, the values of the dimensions are also checked.

In the case of the `N_VALUES $n$`  dimensions allowed in the bio-argo files, any numeric digits will be accepted for " $n$ " and the value will be checked to ensure it matches " $n$ ".

A missing dimension, an extra dimension, or a dimension with an incorrect value will cause a file to be rejected.

3. Variables: The variables specified in the User's Manual, and only those variables, must be present in the data file. Additionally, the variable's data type and dimensions must match the specification. (Special rules apply to "physical parameter" - `<PARAM>` - variables, as described below.)
4. Variable attributes: The variable attributes specified in the User's Manual must be present in the data file. Further, the value of the attributes must match the specification.

NOTE on additional attributes:

The FileChecker only ensures that all of the specified variable attributes exist in the file. Extra attributes are accepted by the FileChecker (and are not checked).<sup>1</sup>

#### 3.1 Physical Parameter Variables

Physical parameters are implemented as netCDF variables (with attributes) in the profile and trajectory files. The list of allowed physical parameter variable names (the `<PARAM>` variables) and their

---

<sup>1</sup> Allowing additional (unchecked) attributes was discussed and approved at ADMT-16. For future reference, the options presented were: 1) develop a list of approved "additional parameters" with the added manual overhead of maintaining the list or 2) allow any and all additional attributes. Option 2 is currently implemented.

associated attributes are documented in the User’s Manual prior to manual-version 3.1. Starting with manual-version 3.1 the list of allowed physical parameter variables is maintained in a separate document; see User’s Manual v3.1 (or later) for the link to the list. This list also specifies the approved attribute settings for each variable.

There are 3 categories of physical parameters: core, bio, and intermediate.

- Core and bio parameters: All six of the *<PARAM>*-related variables must exist in the file: *PROFILE\_<PARAM>\_QC*, *<PARAM>*, *<PARAM>\_QC*, *<PARAM>\_ADJUSTED*, *<PARAM>\_ADJUSTED\_QC*, *<PARAM>\_ADJUSTED\_ERROR* for each parameter.
- Intermediate parameters: For each parameter, the following combinations of *<PARAM>*-related variables are allowed:
  - *The “QC group”*: The three variables can be present together: *PROFILE\_<PARAM>\_QC*, *<PARAM>*, *<PARAM>\_QC*.
  - *The “full group”*: All six variables (as detailed above) exist in the file.

Physical parameter “statistics variables” in bio-argo files: For each *<PARAM>* in a float’s core- and bio-file, two additional variables are allowed *in the bio-profile file*: *<PARAM>\_STD* and *<PARAM>\_MED*.

#### **NOTE on “C\_format”, “FORTRAN\_format” and “resolution” attributes:**

These attributes are *required* for each physical parameter however their settings are sensor dependent and are, therefore, not checked by the FileChecker.

#### **NOTE on “Parameters from duplicate sensors”:**

The User’s Manual (version 3.1, November 7th, 2014) states:

##### **3.3.1 Parameters from duplicate sensors**

Some floats are equipped with 2 different sensors, measuring the same physical parameter. In that case, add the integer “2” at the end of the code of the duplicate parameter (e.g. DOXY2). If more sensors that measure the same physical parameter are added, then the integer will simply increase by 1 (i.e. DOXY3, DOXY4, and so on).

The names of some of the bio-argo parameters end with a numeric digit. In order to avoid confusion, the following standard has been adopted: When a parameter name ends with a numeric digit, insert an underscore (“\_”) between the name and the integer suffix when creating the parameter name for the duplicate sensor. (For example, “BBP700\_2”)<sup>2</sup>

## **3.2 Exceptions**

Exceptions to format rules are discouraged. However, some exceptions are allowed for historical reasons.

Allowed exceptions are described in the appendices.

## **4 Meta-data Data Consistency Checks**

<sup>2</sup> The change to the naming rules for duplicate sensors was discussed and approved at ADMT-16.

## 4.1 Reasonable Date Checks

“Reasonable date checks” are applied in an attempt to ensure that all of the dates in the file are consistent. Subtle problems cannot be detected but hopefully large errors can be caught and corrected.

Note that cross-file checks – comparing data in meta-data files with profile files, etc – are *not* performed.

Variable	Required Conditions	Result (not met)
DATE_CREATION	Set and valid date.	Reject
	After 1997-01-01.	Reject
	Before time file submitted to GDAC.	Reject
DATE_UPDATE	Set and valid date.	Reject
	Not before DATE_CREATION	Reject
	Before time submitted to GDAC.	Reject
LAUNCH_DATE	Valid date.	Reject
	After 1997-01-01.	Reject
START_DATE	If set	
	<ul style="list-style-type: none"> <li>Valid date</li> </ul>	Reject
	<ul style="list-style-type: none"> <li>Not before LAUNCH_DATE</li> </ul>	Warning
STARTUP_DATE	If set	
	<ul style="list-style-type: none"> <li>Valid date</li> </ul>	Reject
END_MISSION_DATE	If set	
	<ul style="list-style-type: none"> <li>Valid date</li> </ul>	Reject
	<ul style="list-style-type: none"> <li>Not before LAUNCH_DATE</li> </ul>	Warning
	<ul style="list-style-type: none"> <li>LAUNCH_DATE set</li> </ul>	Warning

## 4.2 Highly-desirable Parameter Checks (file-version 2.3 and earlier)

The User’s Manual specifies a list of highly-desirable parameters for format-versions up to v2.3. Each of the variables specified in the table are checked for compliance to the stated requirement. Any non-compliant variables generate warnings and do *not* prevent the file from being distributed on the GDAC.

## 4.3 Mandatory Parameter Checks (file version 2.4 and later)

Format-version 2.4 and later meta-data files have mandatory parameters specified in the User’s Manual. Any non-compliant variables generate an *error* and the file is rejected by the GDAC.

Variables with multiple entries (array variables such as the PARAMETER\_\* and SENSOR\_\* variables) have all elements of the arrays checked for compliance. These are: PARAMETER, PARAMETER\_UNITS, PARAMETER\_SENSOR, PREDEPLOYMENT\_CALIB\_COEFFICIENT, PREDEPLOYMENT\_CALIB\_EQUATION, SENSOR, SENSOR\_MAKER, SENSOR\_MODEL, POSITIONING\_SYSTEM, and TRANS\_SYSTEM.

NOTE: Format-version v3.1 also has one highly-desirable parameter (BATTERY\_PACKS) that will only generate a *warning* if it is non-compliant.

## 4.4 Configuration Parameter Name Checks

Configuration parameters were added in format-version 2.4. The FileChecker compares the configuration parameter name entries (LAUNCH\_CONFIG\_PARAMETER\_NAME and CONFIG\_PARAMETER\_NAME) to the list of approved names.

The configuration parameter entries are composed of two parts: the parameter name (everything up to the last “\_”) and the units (everything after the last “\_”). The FileChecker “decomposes” the entries into the name and unit parts and compares the each part to the currently approved lists. The allowed parameter names are documented in reference tables 18. The approved units are the same as those used for the TECHNICAL\_PARAMETER\_NAME and are documented in reference table 14b.

The values of CONFIG\_PARAMETER\_VALUE, CONFIG\_MISSION\_NUMBER, and CONFIG\_MISSION\_COMMENT are not checked.

The configuration parameter specifications can be a “template” similar to:

- CONFIG\_<PARAM>Offset
- CONFIG\_Ocr<param>Bandwidth<I>
- CONFIG\_<short\_sensor\_name>BetaAngle
- CONFIG\_<short\_sensor\_name>DepthZone<N>PowerAcquisitionMode
- CONFIG\_<short\_sensor\_name><param>FluorescenceEmissionBandwidth

In these cases, the “<\*>” section can be replaced with anything or, in fact, nothing (it can be left out).

**\*\*\*FOR FUTURE IMPLEMENTATION\*\*\*** A future enhancement of the FileChecker will apply checks to some or all of these “templates”. For instance, a list of approved “short\_sensor\_names” have been developed (and will be published soon) that the settings can be checked against. The transition from “old names” to “new names” is now supported: Names and units that are deprecated can be defined. Files that contain the deprecated name/unit will still be accepted, but a WARNING will be issued. At the end of the transition period, files with the deprecated name/unit will be REJECTED.

## 5 Profile Data Checks

Both core-Argo and bio-Argo profile files are subject to the following checks. (The core-argo profile files have been checked since the FileChecker was implemented in April 2015. The bio-Argo profile files were added in December 2015.)

### 5.1 Meta-data (within a profile file) Checks

The profile meta-data that is contained within the file is checked for valid settings.

Variable	Required Conditions	Result (not met)
CYCLE_NUMBER	Set.	Reject
	All the same in a single-cycle file.	Reject
DATA_MODE	'A', 'D', or 'R'	Reject
DIRECTION	'A' or 'D'.	Reject
DATA_STATE_INDICATOR	Reference table 6.	Reject
	R-mode file: Not "2C" or "2C+"	Reject
	D-mode file: "2C" or "2C+"	Reject

DATA_CENTRE	Reference table 4. Valid for DAC submitting file.	Reject Reject
INST_REFERENCE	Set.	Warning (V2.3, earlier)
PARAMETER_DATA_MODE	'A', 'D', 'R', or ''	Reject
PLATFORM_NUMBER	5- or 7-digit number. All the same in a single-cycle file.	Reject Reject
POSITIONING_SYSTEM	Reference table 9.	Warning (V2.3, earlier)
WMO_INST_TYPE	Set. Reference table 8.	Reject Reject
JULD_QC	Reference table 2.	Reject
POSITION_QC	Reference table 2.	Reject

## 5.2 Reasonable Date Checks

“Reasonable date checks” are applied in an attempt to ensure that all of the dates in the file are consistent. Subtle problems cannot be detected but hopefully large errors can be caught and corrected.

Note that cross-file checks – meta-data dates with profile dates, etc – are *not* performed.

Variable	Required Conditions	Result (not met)
REFERENCE_DATE_TIME	Set and matches Argo standard.	Reject
DATE_CREATION	Set and valid date.	Reject
	After 1997-01-01.	Reject
	Before time file submitted to GDAC.	Reject
DATE_UPDATE	Set and valid date.	Reject
	Not before DATE_CREATION	Reject
	Before time submitted to GDAC.	Reject
JULD	If missing, JULD_QC = 3, 4, or 9	Reject
	After 1997-01-01.	Reject
	Not after DATE_CREATION	Reject
	Not after GDAC receipt time	Reject
JULD_LOCATION	If set, within 2 days of JULD.	Warning
	If FillValue, position FillValue too.	Reject
HISTORY_DATE	If set, valid date.	Reject
	Not after DATE_UPDATE.	Reject
CALIBRATION_DATE	If set, valid date.	Reject
	Before DATE_UPDATE.	Reject

## 5.3 Physical Parameter Checks

The following checks are performed on the variables associated with the physical parameter data. Failed checks result in *rejection* unless otherwise noted. See section 2.1 for a description of the rules regarding which of the physical parameter variables are allowed/required for each physical parameter.

### STATION\_PARAMETERS:

- All valid parameter names. Reference table 3.
- For each parameter, <PARAM> variable exists in file.
- For each <PARAM> variables (with data), parameter name included in STATION\_PARAMETERS
- Core-file / profile #1: PRES and TEMP present
- No duplicate names in list.
- Blank entries within the sequence of names. (For example, “PRES”, “ “, “TEMP”). Warning

### <PARAM> / <PARAM>\_QC:

- No NaNs
- Valid QC flags: Reference table 2 or blank (“ “; not measured).
- Where data is FillValue: QC flag of 9 or “ “.
- Where QC is 9 or “ “ (not measured), <PARAM> must be FillValue.
- Where data not FillValue:  $1 \leq \text{QC flag} \leq 4$
- Exception: 0 allowed for variables without defined quality control checks (e.g. bio-Argo parameters)

*Note: Some bio-argo parameters have an “extra dimension” - <param>(N\_PROF, N\_LEVELS, N\_VALUESnn). For these variables, a level is only considered to be “FillValue” if all of the “extra dimension” values are FillValue.*

### <PARAM>\_ADJUSTED / <PARAM>\_ADJUSTED\_QC:

- DATA\_MODE = ‘R’: All FillValue (including \*\_QC and \*\_ERROR)
- DATA\_MODE = ‘A’
  - No NaNs (including \*\_ERROR)
  - Valid QC flags: Reference table 2 or blank (“ “; not measured).
  - Where <PARAM>\_ADJUSTED\_QC = “ “ (not measured)
    - <PARAM>\_QC = “ “ and <PARAM>\_ADJUSTED = FillValue
  - <PARAM>\_ADJUSTED\_ERROR set to FillValue for core-parameters. (<PARAM>\_ADJUSTED\_ERROR may be set for bio-parameters.
  - Where <PARAM> is FillValue, <PARAM>\_ADJUSTED, \*\_QC is FillValue

- DATA\_MODE = 'D'
  - No NaNs (including \*\_ERROR)
  - Valid QC flags: Reference table 2 or blank (""; not measured).
  - Where <PARAM>\_ADJUSTED\_QC = "" (not measured)
    - <PARAM>\_QC = "" and <PARAM>\_ADJUSTED = FillValue
  - Where <PARAM> is not FillValue and <PARAM>\_ADJUSTED is FillValue
    - QC = 4 or 9
  - Where <PARAM> is not FillValue and <PARAM>\_ADJUSTED is not FillValue
    - QC ≠ 4 or 9
  - Where QC ≠ 4 or 9: <PARAM>\_ADJUSTED\_ERROR is not FillValue
  - <PARAM>\_ADJUSTED and <PARAM>\_ADJUSTED\_ERROR set at the same levels.

### PROFILE\_<PARAM>\_QC:

- Computed based on the value of:
  - DATA\_MODE = 'R': <PARAM>\_QC
  - DATA\_MODE = 'A' or 'D': <PARAM>\_ADJUSTED\_QC
- Data values: Number of levels flagged with something other than '9' or ''
- Good values: Number of levels flagged with 1, 2, 5, or 8

Reported value must match expected value according to reference table 2a.

## 5.4 Additional D-mode File Checks

These additional checks are performed on D-mode files.

Variable	Required Conditions	Result (not met)
DATA_STATE_INDICATOR	Must be "2C" or "2C+"	Reject
PARAMETER	Every parameter in STATION_PARAMETERS must also be in PARAMETER.	Reject
SCIENTIFIC_CALIB_COMMENT	Not empty – all entries.*	Reject
CALIBRATION_DATE	Must be set to a valid date (see "Reasonable Date Checks" above).	Reject

\* NOTE: If all of the parameter data values in a profile are missing (fill value). Then, the SCIENTIFIC\_CALIB\_COMMENT and CALIBRATION\_DATE are allowed to be empty and are not checked. The parameter name must still be present in PARAMETER.

## 6 Technical Data Checks

### 6.1 Meta-data Checks (within technical file)

The meta-data that is contained within the file is checked for valid settings.

Variable	Required Conditions	Result (not met)
PLATFORM_NUMBER	5- or 7-digit number.	Reject
	All the same in a single-cycle file.	Reject
DATA_CENTRE	Reference table 4.	Reject
	Valid for DAC submitting file.	Reject

### 6.2 Reasonable Date Checks

“Reasonable date checks” are applied in an attempt to ensure that all of the dates in the file are consistent. Subtle problems cannot be detected but hopefully large errors can be caught and corrected.

Variable	Required Conditions	Result (not met)
DATE_CREATION	Set and valid date.	Reject
	After 1997-01-01.	Reject
	Before time file submitted to GDAC.	Reject
DATE_UPDATE	Set and valid date.	Reject
	Not before DATE_CREATION	Reject
	Before time submitted to GDAC.	Reject

### 6.3 Technical Parameter Names (format-version 2.4 and later)

TECHNICAL\_PARAMETER\_NAME entries are composed of two parts: the name (everything up to the last “\_”) and the unit (everything after the last “\_”).

The FileChecker “decomposes” the entries into the name and unit parts and compares the each part to the currently approved lists. (reference tables 14a/b).

The technical parameter specification can be a “template” similar to:

- NUMBER\_Ascending<short\_sensor\_name>SamplesDeepAbsolute
- NUMBER\_<short\_sensor\_name>DescentSamplesDepthZone<Z>
- FLAG\_<short\_sensor\_name>Status
- VOLTAGE\_Battery<short\_sensor\_name>
- PRES\_<int>HoursIntoDesentToProfile

In these cases, the “<\*>” section can be replaced with anything or, in fact, nothing (it can be left out).

**\*\*\*FOR FUTURE IMPLEMENTATION\*\*\*** A future enhancement of the FileChecker will apply checks to some or all of these “templates”. For instance, a list of approved “short\_sensor\_names” have been developed (and will be published soon) that the settings can be checked against.

The transition from “old names” to “new names” is now supported: Names and units that are deprecated can be defined. Files that contain the deprecated name/unit will still be accepted, but a WARNING will be issued. At the end of the transition period, files with the deprecated name/unit will be REJECTED.

TECHNICAL\_PARAMETER\_VALUE entries are not checked.

## 6.4 \*\*\*FOR FUTURE IMPLEMENTATION\*\*\* Technical Parameter Values

\*\*\*This check was discussed at ADMT-16. It was generally agreed that this is useful but it is prioritized below the trajectory data checks and will be implemented at a later date\*\*\*

The currently approved list of Technical Parameter Units includes the “data type” of values associated with that unit. The TECHNICAL\_PARAMETER\_VALUE is checked to ensure that it agrees with the specified type.

Data Type	Valid Value
date/time	Valid date/time string matching the indicated format.
hex	Valid hex characters: 0-9, a-f
integer	Optional leading sign and numeric digits
float	Valid floating point number
string	Any string of characters (no real check)

## 7 Trajectory Data Checks

### 7.1 Meta-data Checks

The meta-data that is contained within the file is checked for valid settings.

Variable	Required Conditions	Result (not met)
DATA_STATE_INDICATOR	Reference table 6. R-mode file: Not "2C" or "2C+" D-mode file: "2C" or "2C+"	Reject Reject Reject
DATA_CENTRE	Reference table 4. Valid for DAC submitting file.	Reject Reject
FIRMWARE_VERSION	Set.	Reject
FLOAT_SERIAL_NUMBER	Set.	Reject
PLATFORM_NUMBER	5- or 7-digit number.	Reject
PLATFORM_TYPE	Reference table 23.	Reject
POSITIONING_SYSTEM	Reference table 9.	Reject
TRAJECTORY_PARAMETERS	All valid parameter names. Reference table 3. For each parameter, <PARAM> variable exists in file. For each <PARAM> variables (with data), parameter name included in TRAJECTORY_PARAMETERS	Reject Reject Reject

	No duplicate names in list.	Reject
	Blank entries within the sequence of names. (For example, "PRES", " ", "TEMP").	Reject
WMO_INST_TYPE	Set.	Reject
	Reference table 8.	Reject

## 7.2 Reasonable Date Checks

“Reasonable date checks” are applied in an attempt to ensure that all of the dates in the file are consistent. Subtle problems cannot be detected but hopefully large errors can be caught and corrected.

Note that cross-file checks – meta-data dates with profile dates, etc – are *not* performed.

Variable	Required Conditions	Result (not met)
REFERENCE_DATE_TIME	Set and matches Argo standard.	Reject
DATE_CREATION	Set and valid date.	Reject
	After 1997-01-01.	Reject
	Before time file submitted to GDAC.	Reject
DATE_UPDATE	Set and valid date.	Reject
	Not before DATE_CREATION	Reject
	Before time submitted to GDAC.	Reject
HISTORY_DATE	If set, valid date.	Reject
	Not after DATE_UPDATE.	Reject

## 7.3 N\_MEASUREMENT Variable Group Checks

**SEE VERSION 2.5 (DRAFT) FOR THE PROPOSED DEFINITIONS OF THESE CHECKS**

---

## Appendix A. Allowed exceptions

### DATA\_TYPE settings:

The approved (documented) DATA\_TYPE settings are:

- Argo meta-data
- Argo profile
- Argo profile merged
- Argo trajectory
- Argo technical data
- B-Argo profile
- B-Argo trajectory

The following exceptions are currently being allowed (because DACs are using them):

- ARGO profile
- ARGO trajectory
- Argo technical
- ARGO technical data

Warnings are currently being sent to DACs for these exceptions.

### Pre-v3.1 Files

Several exceptions have been allowed over the years for various attributes in pre-V3.1 files. Since these files are being replaced by v3.1 files, it is not necessary to document them.

### V3.1 Files

See DATA\_TYPE above.

Global attributes:

- :user\_manual\_version = 3.<anything>;
- :Conventions = Argo-3.<anything> CF-<anything>;

DOXY attributes:

- valid\_min and valid\_max where changed
  - Previous values:
  - Current values
- WARNINGS are being sent to DACs that still use the old values